

Overview

Models

HP 870 Unified Wired-WLAN Appliance

JG723A

Key features

- Enterprise-scale capacity, performance, and high reliability for wireless networks
- System-wide approach to WLAN reliability through Wi-Fi Clear Connect
- IEEE 802.11ac-ready
- Flexible forwarding modes
- Comprehensive feature set for demanding Enterprise environments

Product overview

The IEEE 802.11ac-ready HP 870 Unified Wired-WLAN Appliance delivers enterprise-scale features, capacity, and high reliability, as well as offering substantial data processing capacity for wireless networks.

The HP 870 Unified Wired-WLAN Appliance provides 24 1000 Mb/s Ethernet ports and four 10GbE ports and can optionally support up to 1,536 managed APs, 30,000 users, and 40G of centralized throughput.

The HP 870 Unified Wired-WLAN Appliance provides refined user control and management, comprehensive RF management and security mechanisms, fast roaming, QoS and IPv4/IPv6 features, and powerful WLAN access control.

Features and benefits

Management

- **Wi-Fi Clear Connect**
provides a system-wide approach to help ensure WLAN reliability by proactively determining and adjusting to changing RF conditions and by identifying rogue activity and enforcing prevention policies, and optimizing WLAN performance by detecting interference from Wi-Fi and non-Wi-Fi sources using Spectrum Analysis capabilities built into specific HP access points (refer to the HP Access Point—Controller Compatibility Matrix).
- **Advanced radio resource management**
 - Automatic radio power adjustments include real-time power adjustments based on changing environmental conditions and signal coverage adjustments
 - Automatic radio channel provides intelligent channel switching and real-time interference detection
 - Intelligent client load balancing balances the number of clients across multiple APs to optimize AP and client throughput
 - Airtime fairness helps ensure equal RF transmission time for wireless clients
- **Spectrum Analysis**
 - Signal detection/classification identifies source of RF interference, for example, Bluetooth, cordless phones, and microwave ovens
 - Evaluation of channel quality helps detect severe channel degradation and improves the reporting of poor RF performance
- **Band Navigation**
enables automatic redirection of 5 GHz-capable clients to the less-congested 5 GHz spectrum
- **Enterprise network management**
is provided by HP Intelligent Management Center (IMC) Platform software and the IMC Wireless Services Manager Software Module, which effectively integrate traditionally disparate management tools into one easy-to-use interface

Overview

- **Secure controller management**
manages the controller securely from a single location with IMC or any other SNMP management station; controller supports SNMPv3 as well as SSHv2 and SSL for secure CLI and Web management; console port is available as a pass-through to the switch console function
- **VLAN pooling**
 - enables wireless clients to be dynamically assigned to different VLANs so administrators can assign different subnets to different clients in the same SSID. A VLAN pool can bind to multiple SSIDs.
- **Unified network visibility**
 - provides visibility between a wired and wireless network using IEEE 802.1AB Link Layer Discovery Protocol (LLDP) and sFlow.
- **AP Plug and Play (PnP)**
 - provides zero-configuration capability. An AP without a predefined configuration file can connect to the WLAN controller and the WLAN Controller will provision it with the correct wireless configuration.
- **Policy based forwarding**
 - simplifies the deployment of centralized or local forwarding. The policy-based mode allows user to classify data traffic based on ACL and choose local or centralized forwarding. Policy-based forwarding can be applied based on SSID or user profile. That means a forwarding policy can be applied on a SSID or a specific user or a group of users.
- **AP grouping**
 - enables an admin to easily apply AP-based or radio-based configurations to all the AP that are in the same group.
- **Staged Firmware Upgrades**
 - enables an admin to selectively upgrade APs, typically a group of APs, to minimize the impact of upgrading large deployments of APs to a new version of firmware.
- **Custom antenna settings**
 - allow the admin to select a custom antenna gain.

Quality of Service (QoS)

- **IEEE 802.1p prioritization**
delivers data to devices based on the priority and type of traffic
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **End-to-end QoS**
 - the HP 870 Unified Wired-WLAN Appliance supports the DiffServ standard and IPv6 QoS; the QoS DiffServ model includes traffic classification and traffic policing, and fully implements

Security

- **Web-based authentication**
provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
- **IEEE 802.1X and RADIUS network logins**
supports port-based and SSID-based IEEE 802.1X authentication and accounting
- **WEP, WPA2, or WPA encryption**
can be deployed at the AP to lock out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of wireless traffic
- **Integrated Wireless Intrusion Detection System (WIDS)**
provides support for hybrid and dedicated modes; detects flood, spoofing, and weak IV attacks; displays statistics (events) and history; supports configuration of detection policies
- **Integrated Wireless Intrusion Prevention System (WIPS)**

Overview

- automatically identifies and classifies all APs and stations; enables packet-trigger containment via knowledge-based heuristics; protects against honeypot attacks and enforces STA security; detects Denial Of Service (DoS) attacks via pre-defined DoS attacks, and provides a Signature mechanism which allows admins to define custom rules; enables Virtual Service Domains to deploy security policies by department or location for example.
- **Media access control (MAC) authentication**
provides simple authentication based on a user's MAC address; supports local or RADIUS-based authentication
- **Secure user isolation**
virtual AP services enable network administrators to provide specific services for different user groups, allowing effective resource sharing, and simplifying network maintenance and management
- **Secure access by location**
AP location-based user access control helps ensure that wireless users can access and authenticate only to preselected APs, enabling system administrators to control the locations where a wireless user can access the network
- **Endpoint Admission Defense**
integrated wired and wireless Endpoint Admission Defense (EAD) helps ensure that only wireless clients who comply with mandated enterprise security policies can access the network, reducing threat levels caused by infected wireless clients and improving the overall security of the wireless network
- **Public Key Infrastructure (PKI)**
is used to control access
- **Authentication, authorization, and accounting (AAA)**
uses an embedded authentication server or external AAA server for local users
- **Wireless Intelligent Application Aware Feature (WIAA)**
 - provides a user role based or SSID based firewall embedded in WLAN Controller via ACL-based packet filter firewall and ASPF firewall.
 - Protect clients from outside attacks Restrict specific users from accessing specific network resources.
- **Source Address Validation Improvement (SAVI)**
 - records the wireless client's IP address and MAC address and at the next data traffic forwarding stage, SAVI will validate the client's IP address

Connectivity

- **Loopback**
supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **IPv6**
 - IPv6 host enables controllers to be managed and deployed at the IPv6 network's edge
 - Dual stack (IPv4 and IPv6) transitions customers from IPv4 to IPv6, supporting connectivity for both protocols
 - MLD snooping directs IPv6 multicast traffic to the appropriate interface, preventing traffic flooding
 - IPv6 ACL/QoS supports ACL and QoS for IPv6 network traffic
- **NAT support**
 - NAT traversal helps ensure that communication between a branch office AP and HP 870 is supported when the branch uses NAT.
 - Integrated NAT support replaces the private source IP address with a public address; enables multiple internal addresses to be mapped to the same public IP address; permits only certain internal IP addresses to be NATed, and provides an Application Layer Gateway that supports specific application protocols without requiring the NAT platform to be modified.
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP)**
supports a total of a 128 trunk groups with each group supporting 8 active ports. Ports must be of the same type (that is, all 100/1000 ports or 10GbE ports).

Performance

- **Flexible forwarding modes**

Overview

- enable distributed and centralized traffic forwarding centralized forwarding, wireless traffic is sent to the HP 870 for processing. With distributed mode wireless traffic is dropped off locally. In the event that connectivity to the HP 870 is lost, authenticated clients can continue to access local resources.
- support local drop off or centralization of data traffic after an HTML authentication using the built-in portal server or IMC portal authentication.
- **Wireless user access control and management**
 - support defining settings such as Committed Access Rate (CAS), QoS profiles, and access control policies based on location for different applications.
- **Fast roaming**
supports Layer 3 roaming and fast roaming, satisfying the most demanding voice service requirements
- **Robust capacity**
 - delivers powerful forwarding capacity to support large enterprise WLANs.

Resiliency and high availability

- **High reliability**
supports 1+1, N+1, and N+N backup; the 1+1 redundancy configuration of the modules supports subsecond-level failure detection; APs establish AP-module tunnel links with both modules, but only the links to the active module are active; when the active module fails, the heartbeat mechanism between the two modules helps ensure that the standby module can sense the failure in subsecond level and then informs the APs to switch over to it, thus providing service continuity.
- **802.1X hot-backup**
 - enables two controllers to sync 802.1X state information and wireless client's 802.11 information from master to backup. This feature is only supported on the HP 870 and 20G Unified Module.

Layer 2 switching

- **VLAN support and tagging**
supports IEEE 802.1Q with 4,094 simultaneous VLAN IDs
- **Spanning Tree Protocol (STP)**
supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **Port mirroring**
duplicates port traffic (ingress and egress) to a local monitoring port
- **Jumbo packet support**
supports frame sizes up to 9K byte (switch) and up to 4K byte (controller) to improve the performance of large data transfers

Layer 3 routing

- **Static IP routing**
provides manually configured routing for both IPv4 and IPv6 networks

Comprehensive portfolio

- **Access point support**
Refer to the HP Access Point—Controller Compatibility Matrix (<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA5-0345ENW&cc=us&lc=en>).

Scalability

- **Optional 32 or 128 access-point upgrade license**
 - increases support for additional access points from the base 256 AP support without the need to buy additional costly

Overview

- hardware.
- A reduced-cost 128-access point license is available for use on the redundant controller. Refer to the Specifications and Accessories sections for more detail.

Warranty and support

- **Lifetime Warranty 2.0**
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†
- **Electronic and telephone support (for Lifetime Warranty 2.0)**
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to: www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to: www.hp.com/networking/warrantysummary
- **Software releases**
includes all offered software releases for as long as you own the product; to find software for your product, refer to: www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to: www.hp.com/networking/warrantysummary

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765 zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft® Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at: www.hp.com/networking/warranty.

Technical Specifications

HP 870 Unified Wired-WLAN Appliance (JG723A)

I/O ports and slots	12 RJ-45 autosensing 100/1000 ports; Media Type: Auto-MDIX; Duplex: 100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 12 SFP 100/1000 Mb/s ports (IEEE 802.3z Type 1000BASE-X, IEEE 802.3u Type 100BASE-FX) 4 SFP+ 10GbE ports (IEEE 802.3ae Type 10GBASE-ER, IEEE 802.3ae Type 10GBASE-LR, IEEE 802.3ae Type 10GBASE-SR, IEEE 802.3aq Type 10GBASE-LRM)
Additional ports and slots	1 RJ-45 serial console port 1 RJ-45 out-of-band management port
Physical characteristics	Dimensions 17.32(w) x 18.9(d) x 3.47(h) in (44 x 48 x 8.81 cm) (2U height) Weight 29.32 lb (14.5 kg)
Power supplies	2 power supply slots 1 minimum power supply required includes: 1 x JG527A (HP X351 300W 100-240VAC to 12VDC Power Supply)
Memory and processor	Processor Broadcom XLP432 Eight core @ 1.4 GHz, 4 GB flash, 8 GB DDR3 SDRAM
Mounting and enclosure	EIA-standard 19-inch telco rack or equipment cabinet (hardware included)
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 5% to 95%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 5% to 95%, noncondensing Altitude up to 16,404 ft (5 km)
Electrical characteristics	Maximum heat dissipation 887 BTU/hr (935.79 kJ/hr) AC Voltage 100 - 240 VAC DC Voltage -48 to -60 VDC Maximum power rating 260 W Frequency 50/60 Hz
Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; IEC 60950-1; EN 60950-1; FDA 21 CFR Subchapter J
Features	Default supported APs: 256 Maximum supported APs: 1536 (via the optional purchase of the 32 or 128 access point E-LTU) Maximum supported clients and centralized throughput: - 30,000 clients - 40G centralized throughput Maximum supported users via local portal authentication: 6000 Maximum supported users via local authentication (AAA): 3,000 Maximum supported configured SSIDs: 512 Maximum supported ACLs: 32,000 Supported MSM APs are automatically discovered, Comware firmware is loaded, and the APs can be fully managed. AP upgrade license rules for redundant HP 870 Unified Wired-WLAN Appliance deployments - The primary HP 870 Unified Wired-WLAN Appliance's AP count must be increased using the optional HP Unified Wired-WLAN 128 AP E-LTU (JG649AAE) or the HP Unified Wired-WLAN 32 AP E-LTU (JG774AAE).

Technical Specifications

	- The secondary HP 870 Unified Wired-WLAN Appliance's AP count can be increased as needed using the reduced-cost HP Unified Wired-WLAN 128 AP Redundant E-LTU
Emissions	EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; VCCI-3 CLASS A; VCCI-4 CLASS A; ETSI EN 300 386; FCC Part 15 (CFR 47) CLASS A
Immunity	EN EN 55024, CISPR24 & ETSI EN 300 386
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

General protocols

RFC 768 UDP
 RFC 791 IP
 RFC 792 ICMP
 RFC 793 TCP
 RFC 826 ARP
 RFC 854 TELNET
 RFC 855 Telnet Option Specification
 RFC 858 Telnet Suppress Go Ahead Option
 RFC 894 IP over Ethernet
 RFC 950 Internet Standard Subnetting Procedure
 RFC 959 File Transfer Protocol (FTP)
 RFC 1122 Host Requirements
 RFC 1141 Incremental updating of the Internet checksum
 RFC 1144 Compressing TCP/IP headers for low-speed serial links
 RFC 1256 ICMP Router Discovery Protocol (IRDP)
 RFC 1305 NTPv3 (IPv4 only)
 RFC 1321 The MD5 Message-Digest Algorithm
 RFC 1334 PPP Authentication Protocols (PAP)
 RFC 1350 TFTP Protocol (revision 2)
 RFC 1812 IPv4 Routing
 RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 RFC 2104 HMAC: Keyed-Hashing for Message Authentication
 RFC 2246 The TLS Protocol Version 1.0
 RFC 2284 EAP over LAN

RFC 2463 ICMPv6
 RFC 2464 Transmission of IPv6 over Ethernet Networks
 RFC 2465 Management Information Base for IPv6: Textual Conventions and General Group
 RFC 2466, Management Information Base for IP Version 6 - ICMPv6
 RFC 2526 Reserved IPv6 Subnet Anycast Addresses
 RFC 2553 Basic Socket Interface Extensions for IPv6
 RFC 2563 ICMPv6
 RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
 RFC 3315 DHCPv6 (client and relay)
 RFC 3363 DNS support
 RFC 3484 Default Address Selection for IPv6
 RFC 3493 Basic Socket Interface Extensions for IPv6
 RFC 3513 IPv6 Addressing Architecture
 RFC 3542 Advanced Sockets API for IPv6
 RFC 3587 IPv6 Global Unicast Address Format
 RFC 3596 DNS Extension for IPv6
 RFC 4193, Unique Local IPv6 Unicast Addresses
 RFC 4443 ICMPv6
 RFC 4541 IGMP & MLD Snooping Switch
 RFC 4861 IPv6 Neighbor Discovery
 RFC 4862 IPv6 Stateless Address Auto-configuration
 RFC 5095 Deprecation of Type 0 Routing Headers in IPv6

Network management

IEEE 802.11k-2008 (beacon measurement functionality used as part of radio resource management)
 RFC 1155 Structure of Management Information
 RFC 1905 SNMPv2 Protocol Operations
 RFC 2573 SNMPv3 Applications
 RFC 2574 SNMPv3 User-based Security Model (USM)
 RFC 2575 VACM for SNMP
 SNMPv1/v2c

QoS/CoS

RFC 2474 DS Field in the IPv4 and IPv6 Headers
 RFC 2475 DiffServ Architecture
 RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
 RFC 1851 ESP Triple DES Transform
 RFC 2246 Transport Layer Security (TLS)
 RFC 2401 Security Architecture for the Internet Protocol
 RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP)
 RFC 2409 The Internet Key Exchange (IKE)
 RFC 2548 Microsoft Vendor-specific RADIUS Attributes
 RFC 2716 PPP EAP TLS Authentication Protocol
 RFC 2865 RADIUS Authentication
 RFC 2867 RADIUS Accounting Modifications

Technical Specifications

RFC 2644 Directed Broadcast Control
RFC 2864 The Inverted Stack Table
Extension to the Interfaces Group MIB
RFC 2866 RADIUS Accounting
RFC 2869 RADIUS Extensions
RFC 3164 Syslog
RFC 3268 Advanced Encryption Standard
(AES) Ciphersuites for Transport Layer
Security (TLS)
RFC 3619 Ethernet Automatic Protection
Switching (EAPS)
RFC 3636 Definitions of Managed Objects for
IEEE 802.3 Medium Attachment Units
(MAUs)

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2934 Protocol Independent Multicast
MIB for IPv4
RFC 4541 Considerations for Internet Group
Management Protocol (IGMP) and Multicast
Listener Discovery (MLD) Snooping Switches

IPv6

RFC 1350 TFTP
RFC 1881 IPv6 Address Allocation
Management
RFC 1887 IPv6 Unicast Address Allocation
Architecture
RFC 1981 IPv6 Path MTU Discovery
RFC 2292 Advanced Sockets API for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2375 IPv6 Multicast Address
Assignments
RFC 2454, IP Version 6 Management
Information Base - UDP
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-
configuration

MIBs

RFC 1229 Interface MIB Extensions
RFC 1643 Ethernet MIB
RFC 1757 Remote Network Monitoring MIB
RFC 2011 SNMPv2 MIB for IP
RFC 2012 SNMPv2 MIB for TCP
RFC 2013 SNMPv2 MIB for UDP
RFC 2571 SNMP Framework MIB
RFC 2572 SNMP-MPD MIB
RFC 2613 SMON MIB
RFC 2665 Ethernet-Like-MIB
RFC 2674 Definitions of Managed Objects
for Bridges with Traffic Classes, Multicast
Filtering, and Virtual Extensions
RFC 2863 The Interfaces Group MIB
RFC 2932 IP (Multicast Routing MIB)
RFC 2933 IGMP MIB
RFC 4444 Management Information Base
for Intermediate System to Intermediate
System (IS-IS)

Mobility

IEEE 802.11a High Speed Physical Layer in
the 5 GHz Band
IEEE 802.11b Higher-Speed Physical Layer
Extension in the 2.4 GHz Band
IEEE 802.11d Global Harmonization
IEEE 802.11e QoS enhancements
IEEE 802.11g Further Higher Data Rate
Extension in the 2.4 GHz Band
IEEE 802.11h Dynamic Frequency Selection
IEEE 802.11i Medium Access Control (MAC)
Security Enhancements
IEEE 802.11n WLAN Enhancements for
Higher Throughput

NOTE: All of the above standards are now
included in IEEE 802.11-2012

for Tunnel RFC 2867 RADIUS Accounting
Modifications for Tunnel
RFC 3394 Advanced Encryption Standard
(AES) Key Wrap
Algorithm
RFC 3576 Dynamic Authorization Extensions
to RADIUS (Disconnect Message and
Session-time renewal)
RFC 3579 RADIUS Support For Extensible
Authentication Protocol (EAP)
RFC 3580 IEEE 802.1X RADIUS Guidelines
Access Control Lists (ACLs)
Guest VLAN for 802.1x
Secure Sockets Layer (SSL)
SSHv2 Secure Shell
Web Authentication
WPA (Wi-Fi Protected Access)/WPA2

VPN

RFC 2403 The Use of HMAC-MD5-96 within
ESP and AH
RFC 2404 The Use of HMAC-SHA-1-96 within
ESP and AH
RFC 2405 The ESP DES-CBC Cipher
Algorithm With Explicit IV
RFC 2407 The Internet IP Security Domain of
Interpretation for ISAKMP
RFC 2451 The ESP CBC-Mode Cipher
Algorithms

IPSec

RFC 1829 The ESP DES-CBC Transform
RFC 3602 The AES-CBC Cipher Algorithm and
Its Use with IPSec

IKEv1

RFC 3748 - Extensible Authentication
Protocol (EAP)

PKI

RFC 3280 Internet X.509 Public Key
Infrastructure Certificate and Certificate
Revocation List (CRL) Profile

Accessories

HP 870 Unified Wired-WLAN Switch Series accessories

HP 870 Unified Wired-WLAN Appliance (JG723A)

HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X110 100M SFP LC FX Transceiver	JD102B
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X351 300W 100-240VAC to 12VDC Power Supply	JG527A
HP Unified Wired-WLAN 32 AP E-LTU	JG774AAE
HP Unified Wired-WLAN 128 AP E-LTU	JG649AAE
HP Unified Wired-WLAN 128 AP Redundant E-LTU	JG902AAE

To learn more, visit: www.hp.com/networking

© Copyright 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.